

DESCRIPTION :

De Boer DuO Primer is a thin liquid bitumen primer, with good penetration characteristics for different deck types. It is produced from a blend of bitumen, adhesives and solvents, and improves the bond strength between the deck substrate and the bituminous membranes.

APPLICATION :

- The deck has to be clean, dry and free from dust and contaminations. Laitance should be removed if present.
- Stir well before applying the primer.
- Apply **De Boer DuO Primer** in one layer with a brush, a rubber squeegee or an airless sprayer.
- The consumption : 0.10 - 0.30 kg/m² or 0.11 - 0.33 l/m², depending on the porosity of the deck.
- Dry: depending on surface and climate conditions ≤ 3 hours.

PROPERTIES :

- Flash point cc (astm d93) : 40 °C (Pensky Martens)
- Viscosity 40 °C (astm d445) : 46.93 mm²/s
- Density : approx. 0.92 kg/l at 20 °C

PACKING :

- Metal bins of 25 litres.

STOCKING AND HANDLING :

- Store in well ventilated locations; avoid extreme temperatures
- (ideal storage temperature between 10 °C and 20 °C).
- If used in a closed room : provide mechanical ventilation.
- Avoid ignition sources and open fire.
- Life expectancy in a closed and undamaged packing : 24 months after production date.



Material Safety Data Sheet is available on request.

Edition : 12/05/2017



GLUES



ROOF EDGES



VENTILATION / DRAINS /
CABLE DUCT (HVAC)



NAILS &
SCREWS



TOOLS



OTHER
PRODUCTS



de boer
4 your roof