

TECHNICAL DATA SHEET

Enduroflex Roof Edge Profile Classic Plus 60/60

Description & use:

The Classic Plus roof edge profile is a pre-manufactured profile that terminates the waterproofing membrane at the highest edge of the roof in a professional, watertight and wind-uplift resistant manner. The profile is used on top of roof edge curbs of wooden and concrete flat roofs.

Characteristics:

Material Aluminum 2500

Length per profile mm
Width (visible, outside) 60 mm
Fastening zone 45 mm

Dripping edge 15 mm from wall

Installation:

- The waterproofing cap sheet is installed on top of the roof edge curb.
- The profile is fastened at the roof edge on top of the cap sheet.
- The profile and its fixings are covered by another piece of cap sheet.
- · Always refer to the manufacturer's detail drawing.

Advantages:

- Strong, stable and durable profile that increases the durability of the waterproofing system.
- Increases the bonding of the waterproofing to the edge of the roof-deck.
- Special corner design to prevent penetration by horizontal driven rain.
- Available with connection plates, internal and external pre-manufactured welded corners.
- Wind uplift resistant.
- · Corrosion resistant.
- Continuous aesthetical finish.
- Provides a dripping point of 15mm off the wall to prevent water stains to the wall.

Type	Α	В
60/60	60	60





