

DUO PRIMER

DESCRIPTION :

DUO PRIMER is a thin liquid bitumen primer, with good penetration characteristics for different types of deck types. It is produced from using a blend of bitumen, adhesives and solvents, and improves the bond strength between the deck substrate and the bituminous membranes.

APPLICATION :

- The deck has to be clean, dry, dust and containment free. Laitance should be removed if present.
- Stir well for applying the primer.
- Apply DUO primer in one coat with a brush, a rubber squeegee or an airless sprayer.
- The consumption: 0.2 – 0.30 Kg/m² depending on the porosity of the deck.
- Dry : depending on surface and climate conditions < 3 hours

Properties :

Properties	Test method/ classification	Unit	Expressed as	Result
Viscosity	Ford cup 4	sec	MDV	12
Solid content	EN ISO 3251	%	MDV ± 2abs	45
Volumetric mass	DIN 51757, ISO 2811	g/cm ³	MDV ± 3%	0,87
Drying period	EN ISO 1547	Min.	MLV ≤	180
Flash point	DIN 51755	°C	MLV ≥	27

PACKING :

- Metal pails of 25 litres.

STOCKING AND HANDLING:

- Store in well ventilated locations; avoid extreme temperatures (ideal storage temperature between 10°C –20°C)
- If used in a closed room: provide mechanical ventilation.
- Avoid ignition sources and open fire.
- Life expectancy in a closed and undamaged packing : 12 months.



Safety Data Sheet is available on request.



de boer
waterproofing solutions