

# ENDUROFLEX PEDESTAL

*Adjustable Tile / Paving Support*



ACCESSORY  
PRODUCTS

TECHNICAL DATA SHEET

Enduroflex TDS Jan 2024

## DESCRIPTION

The Enduroflex Pedestal is an adjustable pedestal and are perfect for creating both residential and commercial spaces.

Its ergonomics make the Enduroflex Pedestal easy to adjust and allows quick and reliable installation. The enlarged surface of the head of the pedestal is specially adapted for the laying of very thick ceramic tiles, concrete or natural stone pavers or a floor made of wooden or composite boards.

## COMPOSITION

1. Top of the Pedestal  
The top of the pedestal is screwed directly into the base or into the couplers for additional height requirements. The top has a diameter of 170mm and a surface area of 227cm<sup>2</sup>. It can be fitted with various accessories for different applications such as paving, decking or metal grating.
2. Couplers  
Couplers are used to extend the height of the pedestals to the required finished floor level up to 955mm.
3. Base  
The base can be simply positioned or fixed to any compatible substrate. The head the couplers and the base are equipped with a safety interlocking system. The base incorporate 8 holes ensuring complete drainage. Base diameter 197mm, surface area 305cm<sup>2</sup>.
4. Slope Corrector (0 to 5%)  
The U-PH5 Slope Corrector is placed under the base of the pedestal guaranteeing that the pedestal remains vertical and well balanced even at the highest range. It can compensates slopes between 0-5% in 0.5% intervals.



## CHARACTERISTICS

- Copolymer polypropylene (CPP)
- Composition: + / -80% first grade pre-selected recycled PPC, and + / -20% Talc + Masterbatch black
- Designed and manufactured in Europe
- Use of recycled materials exclusively of EU origin
- Resistant to weathering, sea salts, algae and a wide range of chemicals
- Temperature range : -30 C° to +80 C°

